

# 92

## AGJ series

### 92X92X38mm

#### ●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)  
Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 241g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)  
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 241克



#### ●Specification / 詳細規格 \*軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow	Max. Static Pressure	Sound	Weight		
機型	軸承	電壓	操作電壓	電流	轉速	最大風量	最大風壓	噪音	重量		
P/N	B/S/F	V	V	A	RPM	m <sup>3</sup> /min	CFM	mm-H <sub>2</sub> O	In-H <sub>2</sub> O	dBA	g
AGJ09238*12L	B	12	6.0~13.2	0.41	3500	2.13	75.05	9.12	0.36	42.96	241
AGJ09238*12M	B	12	6.0~13.2	1.01	5000	3.22	113.82	18.04	0.71	55.10	241
AGJ09238*12H	B	12	6.0~13.2	1.65	6000	3.90	137.18	25.85	1.02	60.59	241
AGJ09238*12U	B	12	6.0~13.2	2.53	7000	4.57	161.60	34.39	1.35	64.34	241
AGJ09238*24M	B	24	12.0~26.4	0.51	5000	3.22	113.82	18.04	0.71	55.10	241
AGJ09238*24H	B	24	12.0~26.4	0.88	6000	3.90	137.18	25.85	1.02	60.59	241
AGJ09238*24U	B	24	12.0~26.4	1.32	7000	4.57	161.60	34.39	1.35	64.00	241
AGJ09238*24V	B	24	12.0~26.4	1.87	8000	5.15	181.98	43.85	1.73	67.50	241
AGJ09238*24W	B	24	12.0~26.4	2.42	9000	5.77	203.85	54.48	2.14	70.29	241
AGJ09238*48M	B	48	24.0~52.8	0.30	5000	3.22	113.82	18.04	0.71	55.10	241
AGJ09238*48H	B	48	24.0~52.8	0.42	6000	3.90	137.18	25.85	1.02	60.59	241
AGJ09238*48U	B	48	24.0~52.8	0.64	7000	4.57	161.60	34.39	1.35	64.00	241
AGJ09238*48V	B	48	24.0~52.8	0.85	8000	5.15	181.98	43.85	1.73	67.50	241
AGJ09238*48W	B	48	24.0~52.8	1.32	9000	5.77	203.85	54.48	2.14	70.29	241

#### ● Drawing & panel out-cuts/ 圖面及出入風口

#### ● Characteristic Curves/ 特性曲線

