

40

AGE series

40X40X10mm



●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB;sleeve bearing
- Weight / 20g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB;含油軸承
- 重量 / 20克

●Specification / 詳細規格 *軸承/bearing B:雙滾珠/ball bearing F:FMB S:含油承軸/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow		Max. Static Pressure		Sound	Weight
機型	軸承	電壓	操作電壓	電流	轉速	最大風量		最大風壓		噪音	重量
P/N	B/S/F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGE04010*05M	B/F/S	5	3.0~5.5	0.09	4000	0.13	4.76	1.58	0.06	19.67	20
AGE04010*05H	B/F/S	5	3.0~5.5	0.15	6000	0.19	6.83	3.31	0.13	23.04	20
AGE04010*05U	B/F/S	5	3.0~5.5	0.21	8000	0.26	9.32	5.75	0.23	28.63	20
AGE04010*05V	B/F/S	5	3.0~5.5	0.37	10000	0.33	11.58	8.71	0.34	34.36	20
AGE04010*12M	B/F/S	12	6.0~13.2	0.06	4000	0.13	4.76	1.58	0.06	19.67	20
AGE04010*12H	B/F/S	12	6.0~13.2	0.08	6000	0.19	6.83	3.31	0.13	23.04	20
AGE04010*12U	B/F/S	12	6.0~13.2	0.12	8000	0.26	9.32	5.75	0.23	28.63	20
AGE04010*12V	B/F/S	12	6.0~13.2	0.19	10000	0.33	11.58	8.71	0.34	34.36	20
AGE04010*24L	B/F/S	24	12.0~26.4	0.02	4000	0.13	4.76	1.58	0.06	19.67	20
AGE04010*24M	B/F/S	24	12.0~26.4	0.08	8000	0.26	9.32	5.75	0.23	28.63	20
AGE04010*24H	B/F/S	24	12.0~26.4	0.12	10000	0.33	11.58	8.71	0.34	34.36	20

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

